



**SAFETY DATA SHEET**  
VWF SUBSTRATE SOLUTION

Page 1  
Issued: 2005-05-04  
Revision No: 2

**1. IDENTIFICATION OF THE SUBSTANCE / PREPARATION AND OF THE COMPANY / UNDERTAKING**

**Product name:** VWF SUBSTRATE SOLUTION  
**CAS number:** -  
**Product code:** FVIR130  
**Company name:** Axis-Shield Diagnostics Ltd  
Luna Place  
Technology Park  
Dundee  
DD2 1XA  
Scotland  
Tel: +44 (0) 1382 422 000  
Fax: +44 (0) 1382 422 088  
Emergency tel: +44 (0) 1382 422 000

**2. COMPOSITION / INFORMATION ON INGREDIENTS**

**Hazardous ingredients:** METHANOL 10-30%  
EINECS: 200-659-6 CAS: 67-56-1  
[F] R11; [T] R23/24/25; [T] R39/23/24/25

**3. HAZARDS IDENTIFICATION**

**Main hazards:** Harmful by inhalation, in contact with skin and if swallowed. Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

**4. FIRST AID MEASURES (SYMPTOMS)**

**Skin contact:** There may be redness or whiteness of the skin in the area of exposure. Irritation or pain may occur at the site of contact. Absorption through the skin may be fatal.

**Eye contact:** There may be severe pain. The eyes may water profusely.

**Ingestion:** There may be soreness and redness of the mouth and throat. There may be vomiting. Convulsions may occur. There may be loss of consciousness.

**Inhalation:** There may be shortness of breath with a burning sensation in the throat. Absorption through the lungs can occur causing symptoms similar to those of ingestion. Convulsions may occur. There may be loss of consciousness.

**4. FIRST AID MEASURES (ACTION)**

**Skin contact:** Remove all contaminated clothes and footwear immediately unless stuck to skin. Drench the affected skin with running water for 10 minutes or longer if substance is still on skin. Transfer to hospital if there are burns or symptoms of poisoning.

**Eye contact:** Bathe the eye with running water for 15 minutes. Transfer to hospital for specialist examination.

**Ingestion:** Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. If unconscious, check for breathing and apply artificial respiration if necessary. If unconscious and breathing is OK, place in the recovery position. Transfer to hospital as soon as possible.

[cont...]

**SAFETY DATA SHEET**  
VWF SUBSTRATE SOLUTION

**Inhalation:** Remove casualty from exposure ensuring one's own safety whilst doing so. If conscious, ensure the casualty sits or lies down. If unconscious and breathing is OK, place in the recovery position. If unconscious, check for breathing and apply artificial respiration if necessary. If breathing becomes bubbly, have the casualty sit and provide oxygen if available. Transfer to hospital as soon as possible.

**5. FIRE-FIGHTING MEASURES**

**Extinguishing media:** Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

**Exposure hazards:** Toxic. In combustion emits toxic fumes.

**Protection of fire-fighters:** Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

**6. ACCIDENTAL RELEASE MEASURES**

**Personal precautions:** Do not attempt to take action without suitable protective clothing - see section 8 of SDS. Turn leaking containers leak-side up to prevent the escape of liquid.

**Environmental precautions:** Do not discharge into drains or rivers. Contain the spillage using bunding.

**Clean-up procedures:** Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

**7. HANDLING AND STORAGE**

**Handling requirements:** Avoid direct contact with the substance. Ensure there is exhaust ventilation of the area. Avoid the formation or spread of mists in the air.

**Storage conditions:** Store at 2-8°C Keep container tightly closed.

**Suitable packaging:** Must only be kept in original packaging.

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

**Hazardous ingredients:** METHANOL  
TWA (8 hr exposure limit): 266 mg/m<sup>3</sup> STEL (15 min exposure limit): 333 mg/m<sup>3</sup> (OES)

**Engineering measures:** Ensure there is exhaust ventilation of the area.

**Respiratory protection:** Self-contained breathing apparatus must be available in case of emergency.

**Hand protection:** Impermeable gloves.

**Eye protection:** Safety glasses with side-shields. Ensure eye bath is to hand.

**Skin protection:** Impermeable protective clothing.

**9. PHYSICAL AND CHEMICAL PROPERTIES**

**State:** Liquid

**Colour:** Colourless

**Odour:** Perceptible odour

**Oxidising:** Non-oxidising (by EC criteria)

**Solubility in water:** Soluble

**10. STABILITY AND REACTIVITY**

**Stability:** Stable under normal conditions.

**Conditions to avoid:** Heat. Hot surfaces. Flames.

**Materials to avoid:** Strong oxidising agents. Strong acids.

**Haz. decomp. products:** In combustion emits toxic fumes.

**11. TOXICOLOGICAL INFORMATION**

**Hazardous ingredients:** METHANOL  
IVN RAT LD50 2131 mg/kg  
ORL MUS LD50 7300 mg/kg  
ORL RAT LD50 5628 mg/kg

**Routes of exposure:** Refer to section 4 of SDS for routes of exposure and corresponding symptoms.

**12. ECOLOGICAL INFORMATION**

**Mobility:** Readily absorbed into soil.

**Persistence and degradability:** No data available.

**Bioaccumulative potential:** No data available.

**Other adverse effects:** No data available.

**13. DISPOSAL CONSIDERATIONS**

**NB:** The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

**14. TRANSPORT INFORMATION****ADR / RID**

**UN no:** -

**Shipping name:** "NOT SUBJECT TO ADR"

**IMDG / IMO**

**UN no:** -

**IATA / ICAO**

**UN no:** -

**15. REGULATORY INFORMATION**

**Hazard symbols:** Toxic.



**Risk phrases:** R20/21/22: Harmful by inhalation, in contact with skin and if swallowed.  
R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

**Safety phrases:** S23: Do not breathe fumes.  
S28: After contact with skin, wash immediately with plenty of water.

**SAFETY DATA SHEET**  
VWF SUBSTRATE SOLUTION

S36/37/39: Wear suitable protective clothing, gloves and eye / face protection.

S45: In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

S51: Use only in well-ventilated areas.

S63: In case of accident by inhalation, remove casualty to fresh air and keep at rest.

**Note:** The regulatory information given above only indicates the principal regulations specifically applicable to the product described in the safety data sheet. The user's attention is drawn to the possible existence of additional provisions which complete these regulations. Refer to all applicable national, international and local regulations or provisions.

## 16. OTHER INFORMATION

**Other information:** Revision 2 due to reclassification of dimethyl sulphoxide..

**Risk phrases used in s.2:** R11: Highly flammable.

R23/24/25: Toxic by inhalation, in contact with skin and if swallowed.

R39/23/24/25: Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.

**Legal disclaimer:** The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.

